



BL059000 Marine Steering Oil

Document version: Mar 22, 2025



Description

This marine steering oil is a paraffinic oil with a high viscosity index for optimum operation of hydraulic systems with a high varying temperature range. This steering oil provides excellent protection against wear and corrosion, has a good filtration ability and fast de-aeration time resulting in less chance of foaming. It is fully compatible with seal materials such as nitrile, silicone and fluoropolymers (Teflon). MPM Marine Steering Oil is suitable for use in marine hydraulic steering systems including launch boats with Vetus hydrolysis.

According to the specifications of

DIN 51524 part 3
ISO 6743-4 Class HV 22

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| BL059001 | 1 L | 6 | 450 |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|-------|--------------------|
| Density at 15°C | 0.859 | kg/l |
| Kinematic Viscosity at 40°C | 21.6 | mm ² /s |
| Kinematic Viscosity at 100°C | 5 | mm ² /s |
| Viscosity Index | 168 | |
| Flashpoint COC | 186 | °C |
| Pourpoint | -39 | °C |

These characteristics are typical of current production. Variations in these characteristics may occur.