



05000PC-FE Motor Oil 0W-20 Premium Synthetic PC-FE

Document version: May 20, 2024



Description

This Premium Synthetic "MID SAPS" engine oil has been developed for petrol and diesel engines equipped with an exhaust gas aftertreatment system. Highly suitable for extended drain intervals, taking into account the use of bio-components in the fuel. Through better efficiency, this SAE 0W-20 engine oil ensures maximum performance and reduces fuel consumption and is mandatory for the recent engines of PSA, DS and Opel, equipped with BLUE HDi, PureTech that use Stop & Start technology and hybrid engines. The optimized fuel consumption results into lower emissions of CO₂ and particulate matter.

Application manual

According to the specifications of

ACEA C5
Fiat 9.55535-DM1
PSA B71 2010

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001PC-FE	1 L	6	450
05005PC-FE	5 L	4	112
05020PC-FE	20 L	1	30
05060PC-FE	60 L	1	6
05205PC-FE	205 L	1	2
05999PC-FE	1000 L	1	-
P05000PC-FE	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.841	kg/l	ASTM D1298
SAE	0W-20		SAE J300
Kinematic Viscosity at 40°C	43.5	mm ² /s	ISO 3104
Kinematic Viscosity at 100°C	8.3	mm ² /s	ISO 3104
Viscosity Index	170		ISO 2909
Flashpoint	232	°C	NF EN ISO 2592
Pourpoint	-48	°C	NF T 60 105

These characteristics are typical of current production. Variations in these characteristics may occur.